

VoIP Video Intercom

The CyberData SIP-enabled Video Intercom is a Power-over-Ethernet (PoE 802.3af) and Voice-over-IP (VoIP) two-way access control device that allows you to communicate and monitor entry areas. The intercom is compatible with most SIP-based IP PBX servers and supports most SIP-based Video phones and SIP clients that support the SIP Video standard.

Typical Applications

- Access control
- Video security

Features

- PoE 802.3af enabled (Powered-over-Ethernet)
- SIP compliant
- Dual-speed Ethernet 10/100 Mbps
- Adaptive full-duplex voice operation
- Network adjustable speaker volume
- Network adjustable microphone sensitivity
- Network downloadable firmware
- Dry relay contact for auxiliary control
- Door closure and tamper alert signals
- Color camera
- IP-42-rated enclosure

The following Intercom models are also available:



Outdoor Intercom
#010935



Indoor Intercom
#011111



Emergency Intercom
#011035



Wall Mount Keypad
#011113



Flush Mount Keypad
#011123



Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +5 volts at 1000mA
Operating Temperature	-30 to 55 C (-22 to 131 F)
Payload Types	G711, A-law and μ -law
Regulatory Compliance	FCC Class A, UL 60950
Dimensions	5" x 5" x 2.5" (H x W x D)
Camera type	1/3 inch CCD Color
Resolution	Wide VGA (720x480), VGA, QVGA, CIF, and QCIF at 30fps
Video Encoding	H.264
Sensitivity	1 lux
Angular Field of Vision	158 degrees diagonal
Warranty	2 years limited
Part Number	011020

VoIP Video Intercom

